

PT Series

Features

- 1. Size: According to customer's installation requirements
- 2. Linearity (%): 0.1, 0.2, 1.0
- 3. Operating frequency: 20KHz---500KHz
- 4. Electrical resistance: 3000VAC 1mA 60S
- 5. Encapsulation method: filled with flame-retardant epoxy resin
- 6. Compliance: RoHS
- ★ Customizable According to Customer Requirements

Application areas

- 1. Power Supply: PD Power Supply, Outdoor Power Supply, Mobile Phone /Laptop Charger, LED Driver Power Supply, Computer Switching Power Adapter.
- 2. Household Appliances: TV, air Conditioner, Refrigerator, Audio Equipment, Lighting Equipment.
- 3. Industrial and Power Equipment: Charging Piles, High-Frequency Inverter Welding Machines, UPS Uninterruptible Power Supplies, Photovoltaic Inverters, and Wind Power Converters.

PT 系列



功能特性

- 1.尺寸：根据客户安装需求
- 2.线性度（%）：0.1，0.2，1.0
- 3.工作频率：20KHz---50KHz
- 4 抗电强度：3000VAC 1mA 60S
- 5 封装方式：阻燃环氧树脂灌封
- 6.符合：RoHS
- ★可根据客户要求定制



应用领域

- 1. 电源：PD 电源、户外电源、手机/笔记本充电器、LED 驱动电源、电脑开关电源适配器。
- 2. 家用电器：电视、空调、冰箱、音响、照明设备。
- 3. 工业与电力设备：充电桩、高频逆变电焊机、UPS 不间断电源、光伏逆变器、风电变流器。

Shape and Dimensions(dimensions are in mm) 外观与尺寸



立式



卧式

Spec 规格	A	B	C	D	E	Operating Frequency 工作频率	Shape 形状
PT01	20.0 Max	21.0 Max	21.5Max	10.3±0.5	12.7±0.5	20kHz-500KHz	卧式
PT01B	20.5 Max	18.0 Max	20.0 Max	10.0±0.5	12.7±0.5	20kHz-500KHz	卧式
PT02	27.0 Max	18.5 Max	32.0 Max	6.0±0.5	15.0±0.5	20kHz-500KHz	立式
PT04	27.5 Max	27.5 Max	21.5 Max	10.0±0.5	20.0±0.5	20kHz-500KHz	卧式

<http://www.easehouse.com.hk>